

# LifeWindow™ One

Veterinary Multi-Parameter Physiologic Monitor

*Superior Veterinary Monitoring  
Meets Portability*



## Gold standard veterinary measurements

- 3/5 Lead Digicare™ VetECG™
- Masimo® SET® Rainbow® oximetry with PVI®
- Capnography with optional Anesthetic Agents
- SunTech® VetBP® Blood Pressure
- Temperature
- Up to 8 hours battery life

*Driven by Innovation ...  
... in Veterinary Medicine*  
[www.digi-vet.com](http://www.digi-vet.com)



# LifeWindow™ One

## Veterinary Multi-Parameter Physiologic Monitor

Digicare's new LifeWindow™ One is a portable veterinary specific physiological monitor with distinctive features and benefits. Engineered with premium veterinary specific modules including an easily operated touch screen user interface. This monitor is in a class of its own, compact and weighing only 3 Lbs. Made with convenience in mind, the LifeWindow™ One can be easily mounted on a rolling stand or IV pole. The perfect combination of size and functionality to complement any hospital (clinic) setting.



All monitors ordered with only 1 parameter will include a plug & play connector for either Masimo CO2 or SpO2 for upgrade at any time. All models come standard with a port to measure temperature. Select up to any 2 parameters of your choice see chart below.

	Code	Module Name	Internal	Plug & Play
ECG	E	3/5 Lead Digicare™ VetECG™	✓	
	Sm	Masimo® SET® Rainbow® SpO2	✓	
SpO2	Sp	Masimo® SET® SpO2		✓
	Sh	Nonin® SpO2	✓	
	Sn	Nellcor® OxiMax®	✓	
	Cmi*/Cme**	Masimo® Side-Stream Capnography	✓	✓
GAS	Gmi*/Gme**	Masimo® Side-Stream Anesthetic Agents	✓	✓
	Mme**	Masimo® Main-Stream Capnography	✓	✓
	Mgme**	Masimo® Main-Stream Anesthetic Agents		✓
	Cri*/Cre**	Respironics® Side-Stream Capnography	✓	✓
	Mre**	Respironics® Main-Stream Capnography		✓
	Port Temp NIBP	N	Suntech® VetBP® Non-Invasive Blood Pressure	✓
T		Temperature	✓	
Port	PP3RM	Dual Monitors only additional port for plug & play Respironics CO2 and/or Masimo CO2/SpO2		✓

\* Internal Module \*\* External Module

Part # example of LW One with CO2 Plug & Play Masimo Mainstream, NIBP and temperature port: LW ONE MmN

### General Specifications

Display Type - 480x272 4.8" LED backlit TFT screen

Mains Voltage - Automatic Selection 100Vac to 240Vac (50/60 Hz)

Battery - Internal Li-ion rechargeable battery


Relative Humidity - 30 to 70% (non condensing)

Dimensions - W 9.14"(232) H 3.46"(88) D 5.67"(144) (mm)

Weight - 3 Lbs (1.4 Kg)

Safety - Meets IEC601-1-1 and IEC 601-1-2

*Driven by Innovation in Veterinary Medicine*



**DIGICARE**  
Animal Health

Digicare Animal Health  
107 Commerce Road  
Boynton Beach, Florida, 33426  
USA  
Phone: 561-689-0408  
Fax: 561-689-0021

Distributed by:



For more information go to:  
[WWW.DIGI-VET.COM](http://WWW.DIGI-VET.COM)  
email: sales@digicarebiomedical.com



**844-4DIGICARE**